

超薄串口(485)系列

- ◇ 快速响应 (50W探头, 0%-95% 响应时间1.5S)
- ◇ 极高损伤阈值。11kW/cm²@40W
- ◇ 波长范围: 0.19-11μm
- ◇ 校正NIST溯源
- ◇ 外形小巧
- ◇ 优化热沉设计, 高承载功率
- ◇ 方形探头, 易集成, 可以方便的安装到设备
- ◇ 线缆长度可定制



Model	Lynk-485-10-HP-25 NEW	Lynk-485-50-HP-25 NEW
Max. Average Power	10W	50W
Min. Power	20 mW	50 mW
Power Resolution	100 mW	10 mW
Noise Equivalent Power (NEP)	500mW	20mW
Response Time	1.5 S	1.5 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25mm
Type	HPB	HPB
Absorber Specs	0.19 - 25 μm	0.19 - 25 μm
Absorber Spectral Range		
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	10m - 485	10m - 485

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright © 2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com allen@huaonelight.com 黄经理 18211550400

超薄串口(485)系列

- ◇ 快速响应 (100W-150探头, 0%-95% 响应时间1.5S)
- ◇ 极高损伤阈值。11kW/cm²@40W
- ◇ 波长范围: 0.19-11μm
- ◇ 校正NIST溯源
- ◇ 外形小巧
- ◇ 优化热沉设计, 高承载功率
- ◇ 方形探头, 易集成, 可以方便的安装到设备
- ◇ 线缆长度可定制



Model	Lynk-485-100-HP-25 NEW	Lynk-485-150-HP-25 NEW
Max. Average Power	100W	150W
Min. Power	80 mW	80 mW
Power Resolution	20 mW	20 mW
Noise Equivalent Power (NEP)	30 mW	30 mW
Response Time	1.5S	1.5S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25 mm
Type	HPB	HPB
Absorber Specs	0.19 - 25μm	0.19 - 11μm
Absorber Spectral Range		
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	10m - 485	10m - 485

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd