

带表头系列/中高功率水冷探头

- ☆ 极高损伤阈值, 5KW/cm²@200W
- ☆ 光谱波长范围: 0.19-11um
- ☆ 校准波长范围: 0.19-2.1um, 2.94um, 9-11um
- ☆ 校正NIST溯源
- ☆ 优化热沉设计, 高承载功率
- ☆ 圆形探头, 易集成, 可以方便的安装到设备
- ☆ 连接方式: 表头LA Pro



Model/型号	LA Pro-WP200-HP-50	LA Pro-WP300-HP-50	LA Pro-WP500-HP-50	LA Pro-WP1000-HP-50
Max.Average Power /最大平均功率	200W	300W	500W	1000W
Min.Power/最小功率	0.1W	0.3W	0.5W	10W
Power Resolution/功率分辨率	0.1W			1W
Noise Equivalent Power /噪声等效功率	0.2W			2W
Response Time/响应时间	2S		5S	
Power Calibration Uncertainty/校准头确定度	±3%			
Power Linearity(1)线性度	±1%			
Aperture/接收口径	50mm			
Type/传感器镀膜层	HPB			
Max.Power Density/损伤阈值	5KW/cm² @200W			
Cooling/冷却方式	水冷			
Dimension/尺寸	90X90X46			
Weight Dimension/重量	2KG			
Cable length-connector /探头线缆长度	2M			