

水冷带表头/千瓦级系列

- ✧ 快速响应 (3000W探头, 0%-95%)
响应时间10S)
- ✧ 极高损伤阈值, 5kW/cm²@200W
- ✧ 波长范围:0.19-11um
- ✧ 校正NIST溯源
- ✧ 外形小巧
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便安装到设备
- ✧ 连接方式: 表头LA Pro



Model	LA Pro-W2000-HP-50	LA Pro-W3000-HP-50
Max. Average Power	2000W	3000W
Min. Power	20W	30W
Power Resolution	1 W	1 W
Noise Equivalent Power (NEP)	1 W	1 W
Power Scales	2000W	3000W
Response Time	10 S	10 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	50mm	50 mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 11 μm	0.19 - 11 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	5kW/cm ² @200 W	5kW/cm ² @200 W
General Characteristics		
Cooling	Water (a)	Water (a)
Minimum and Recommended water flow at full power (b)	8 L/min 11L/min	8 L/min 11L/min
Weight Dimension	2 kg	2 kg
Dimension	90X90X46mm	90X90X46mm
Cable lenght - connector	2m	2m

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd