

超薄2W(USB/RS232)功率计

- ✧ 快速响应 (2W探头, 0%-95%
响应时间1.5S)
- ✧ 极高损伤阈值, 11kW/cm²@40W
- ✧ 波长范围: 0.19-11μm
- ✧ 校正NIST溯源
- ✧ 外形小巧
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便的安装到设备
- ✧ 线缆长度可定制



Model	Lynk-USB-2-HP-25	Lynk-RS232-2-HP-25
Max. Average Power	2W	2W
Min. Power	2 mW	2 mW
Power Resolution	100 uW	1 mW
Noise Equivalent Power (NEP)	200 μW	200 μW
Response Time	1.5 S	1.5 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25 mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 11 μm	0.19 - 11 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m-RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd

超薄10W(USB/RS232)功率计

- ✧ 快速响应 (10W探头, 0%-95% 响应时间0.7S)
- ✧ 极高损伤阈值, 11kW/cm²@40W
- ✧ 波长范围: 0.19-11μm
- ✧ 校正NIST溯源
- ✧ 外形小巧
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便的安装到设备
- ✧ 线缆长度可定制



Model	Lynk-USB-10-HP-25	Lynk-RS232-10-HP-25
Max. Average Power	10 W	10 W
Min. Power	20 mW	20 mW
Power Resolution	100 μW	100 μW
Noise Equivalent Power (NEP)	500 μW	500 μW
Response Time	0.7 S	0.7 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25mm	25mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 11 μm	0.19 - 11 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m - RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com

allen@huaonelight.com

黄经理 18211550400

超薄20W(USB/RS232)功率计

- ✧ 快速响应 (20W探头, 0%-95% 响应时间1.5S)
- ✧ 极高损伤阈值。11kW/cm²@40W
- ✧ 波长范围: 0.19-11μm
- ✧ 校正NIST溯源
- ✧ 外形小巧
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便的安装到设备
- ✧ 线缆长度可定制



Model	Lynk-USB-20-HP-25	Lynk-RS232-20-HP-25
Max. Average Power	20W	20W
Min. Power	20mW	20mW
Power Resolution	1 mW	1 mW
Noise Equivalent Power (NEP)	20mW	20mW
Response Time	1.5 S	1.5 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 11 μm	0.19 - 11 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m-RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright © 2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com allen@huaonelight.com 黄经理 18211550400

超薄30W(USB/RS232)功率计

- ✧ 快速响应 (30W探头, 0%-95%
响应时间1.5S)
- ✧ 极高损伤阈值。11kW/cm²@30W
- ✧ 波长范围: 0.19-11μm
- ✧ 校正NIST溯源
- ✧ 外形小巧
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便的安装到设备
- ✧ 线缆长度可定制



Model	Lynk-USB-30-HP-25	Lynk-RS232-30-HP-25
Max. Average Power	30W	30W
Min. Power	30mW	30mW
Power Resolution	1 mW	1 mW
Noise Equivalent Power (NEP)	20mW	20mW
Response Time	1.5 S	1.5 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25 mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 11 μm	0.19 - 11 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m-RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com

allen@huaonelight.com

黄经理 18211550400

超薄50W(USB/RS232)功率计

- ◇ 快速响应 (50W探头, 0%-95%
响应时间1.5S)
- ◇ 极高损伤阈值。11kW/cm²@40W
- ◇ 波长范围: 0.19-11um
- ◇ 校正NIST溯源
- ◇ 外形小巧
- ◇ 优化热沉设计, 高承载功率
- ◇ 方形探头, 易集成, 可以方便的安装到设备
- ◇ 线缆长度可定制



Model	Lynk-USB-50-HP-25	Lynk-RS232-50-HP-25
Max. Average Power	50W	50W
Min. Power	50 mW	50 mW
Power Resolution	10 mW	10 mW
Noise Equivalent Power (NEP)	20mW	20mW
Response Time	1.5 S	1.5 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25mm
Type	HPB	HPB
Absorber Specs	0.19 - 25 μm	0.19 - 25 μm
Absorber Spectral Range		
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m-RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright © 2017 Shenzhen Huaone Light Co.,Ltd

超薄100W(USB/RS232)功率计

- ✧ 快速响应 (100W探头, 0%-95% 响应时间1.5S)
- ✧ 极高损伤阈值。11kW/cm²@40W
- ✧ 波长范围: 0.19-11μm
- ✧ 校正NIST溯源
- ✧ 外形小巧
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便的安装到设备
- ✧ 线缆长度可定制



Model	Lynk-USB-100-HP-25	Lynk-RS232-100-HP-25
Max. Average Power	100W(150W in 1min)	100W(150W in 1min)
Min. Power	80 mW	80 mW
Power Resolution	20 mW	20 mW
Noise Equivalent Power (NEP)	30 mW	30 mW
Response Time	1.5S	1.5S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25 mm
Type	HPB	HPB
Absorber Specs	0.19 - 25 μm	0.19 - 11μm
Absorber Spectral Range		
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m-RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright © 2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com allen@huaonelight.com 黄经理 18211550400

超薄150W(USB/RS232)功率计

- ◇ 快速响应 (150W探头, 0%-95% 响应时间1.5S)
- ◇ 极高损伤阈值。11kW/cm²@40W
- ◇ 波长范围: 0.19-11μm
- ◇ 校正NIST溯源
- ◇ 外形小巧
- ◇ 优化热沉设计, 高承载功率
- ◇ 方形探头, 易集成, 可以方便的安装到设备
- ◇ 线缆长度可定制



Model	Lynk-USB-150-HP-25	Lynk-RS232-150-HP-25
Max. Average Power	150W	150W
Min. Power	80 mW	80 mW
Power Resolution	20 mW	20 mW
Noise Equivalent Power (NEP)	30 mW	30 mW
Response Time	1.5 S	1.5 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	25 mm	25 mm
Type	HPB	HPB
Absorber Specs	0.19 - 25 μm	0.19 - 11μm
Absorber Spectral Range		
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	11kW/cm ² @40W	11kW/cm ² @40W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2m-USB	2 m-RS232

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright © 2017 Shenzhen Huaone Light Co.,Ltd