

保护镜片



材料

FusedSilica

尺寸

批量可定制

表面平坦度

$\lambda/10@632.8\text{nm}$ in Dia. 25.4mm

透过率

>99.5%

激光损伤阈值

>25J/cm², 10 ns, 10 Hz@1064nm

光洁度

40/20

常规产品

名称	型号	波长	直径mm	厚度mm	透过率	材料
保护镜片	EMC-P-355-25.4*3	355nm	25.4	3	>99.5%	FusedSilica
	EMC-P-355-25.4*5		25.4	5		
	EMC-P-355-30*3		30	3		
	EMC-P-355-60*3		60	3		
	EMC-P-355-80*3		80	3		
	EMC-P-355-87.5*3 (402)		87.5	3		
	EMC-P-355-113*3		113	3		
保护镜片	EMC-P-532-25.4*3	532nm	25.4	3	>99.5%	FusedSilica
	EMC-P-532-80*3		80	3		
	EMC-P-532-76*3 (209)		76	3		
保护镜片	EMC-P-1064-12.7*1	1064nm	12.7	1	>99.5%	FusedSilica
	EMC-P-1064-25*2		25	2		
	EMC-P-1064-25.4*1		25.4	1		
	EMC-P-1064-25.4*3		25.4	3		
	EMC-P-1064-30*5		30	5		
	EMC-P-1064-50.8*3		50.8	3		
	EMC-P-1064-78*3		78	3		
CO2保护镜片	EMC-P-10.6-25.4*3	10.6μm	25.4	3	98%	ZnSe
	EMC-P-10.6-30*3		30	3		