

高灵敏度激光功率计

- ✧ 高分辨率：0.1mW
- ✧ 最小响应功率：2mW
- ✧ 高稳定性：波动小
- ✧ 波长范围：全波段可测
- ✧ 可通过电脑软件读取
- ✧ 极强的抗干扰能力
- ✧ 方形探头，易集成，可以方便安装到设备
- ✧ 连接方式：高精度表头



Model	LA Pro TP-2A-HS-18	LA Pro TP-12A-HS-18
Max. Average Power	2 W	12 W
Min. Power	1 mW	2 mW
Power Resolution	0.1mW	0.1mW
Noise Equivalent Power (NEP)	30mW	50uW
Response Time	3 sec	3 sec
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	18mm	18mm
Type	HS	HS
Absorber Specs		
Absorber Spectral Range	0.19 - 25 μm	0.19 - 25 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 8 - 11 μm	0.19 - 2.1 μm, 2.94μm, 8 - 11 μm
Max Power Density (2)	25kW/cm ² @5W	25kW/cm ² @5W
General Characteristics		
Cooling	Conduction (a)	Conduction
Weight Dimension	0.20 kg	0.20 kg
Dimension	60x 60 x 20 mm	60x 60 x 20 mm
Cable lenght - connector	2 m	2 m

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com

allen@huaonelight.com

黄经理 18211550400