



风冷表头款

- ◇ 快速响应 (150W探头, 0%-95%)
响应时间2 S,稳定时间3 S)
- ◇ 极高损伤阈值, 4kW/cm²
- ◇ 波长范围:0.19-11um
- ◇ 校正NIST溯源
- ◇ 外形小巧, 带风扇
- ◇ 优化热沉设计, 高承载功率
- ◇ 方形探头, 易集成, 可以方便安装到设备
- ◇ 连接方式: 表头LA Por



Model	LA Pro-F50-CP-19	LA Pro-F150-CP-19
Max. Average Power	50 W	150 W
Min. Power	50 mW	100 mW
Power Resolution	0.01 W	0.01 W
Noise Equivalent Power (NEP)	20 mW	0.1 W
Response Time	2S	2S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1.5%	± 1.5%
Aperture	19mm	19mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 11 μm	0.19 - 11 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94μm, 9 - 11 μm
Max Power Density (2)	4kW/cm ²	4kW/cm ²
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	1.0 kg	1.0 kg
Dimension	65 x 65 x 60 mm	65 x 65 x 72 mm
Cable length - connector	2m	2m

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright ©2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com

allen@huaonelight.com

黄经理 18211550400