



风冷表头款

- ✧ 快速响应 (150W探头, 0%-95%)
响应时间1秒,稳定时间2秒)
- ✧ 极高损伤阈值, 22kW/cm²@10W
- ✧ 波长范围:0.19-25um
- ✧ 校正NIST溯源
- ✧ 外形小巧, 带风扇
- ✧ 优化热沉设计, 高承载功率
- ✧ 方形探头, 易集成, 可以方便安装到设备
- ✧ 连接方式: 表头LA Pro



Model	LA Pro-F50-LP1-19	LA Pro-F150-LP1-19
Max. Average Power	50 W	150 W
Min. Power	50 mW	100 mW
Power Resolution	0.01 W	0.01 W
Noise Equivalent Power (NEP)	20 mW	0.1 W
Response Time	1 S	1 S
Power Calibration Uncertainty	± 3%	± 3%
Power Linearity (1)	± 1%	± 1%
Aperture	19mm	19mm
Type	HPB	HPB
Absorber Specs		
Absorber Spectral Range	0.19 - 25 μm	0.19 - 25 μm
Calibration Spectral Range	0.19 - 2.1 μm, 2.94 μm, 9 - 11 μm	0.19 - 2.1 μm, 2.94 μm, 9 - 11 μm
Max Power Density (2)	22kW/cm ² @10W	22kW/cm ² @10W
General Characteristics		
Cooling	Conduction (a)	Conduction (a)
Weight Dimension	1.0 kg	1.0 kg
Dimension	65 x 65 x 60 mm	65 x 65 x 72 mm
Cable length - connector	2 m	2 m

Notes (1). Detector centrally irradiated @50% of useful surface.

(2). Damage thresholds also depend on power level. Please see damage graphs for more details.

Copyright © 2017 Shenzhen Huaone Light Co.,Ltd

www.huaonelight.com

allen@huaonelight.com

黄经理 18211550400